

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

Fiddes Precat Coloured Lacquer

Revision 2

Revision date 2015-07-08

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Fiddes Precat Coloured Lacquer
--------------	--------------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC9a] Coatings and paints, thinners, paint removers; [PROC11] Non industrial spraying; [AC11] Wood articles;
Description	No data is available on this product.

1.3. Details of the supplier of the safety data sheet

Company	Fiddes & Son Ltd
Address	Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX
Web	www.fiddes.co.uk
Telephone	+44 (0)29 2034 0323
Fax	+44 (0)29 2034 3235
Email	info@fiddes.co.uk
Email address of the competent person	info@fiddes.co.uk

1.4. Emergency telephone number

Emergency telephone number	1-352-323-3500
Company	INFOTRAC 24HR

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 67/548/EEC	F; R11 Xn; R48/20-63-65 Xi; R36/38 R66-67 Symbols: F: Highly flammable. Xn: Harmful.
Main hazards	Highly flammable. Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336; STOT RE 2: H373;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Fiddes Precat Coloured Lacquer

Revision 2

Revision date 2015-07-08

2.2. Label elements

Precautionary Statement: Prevention	Skin Irrit. 2: H315 - Causes skin irritation. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H336 - May cause drowsiness or dizziness. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 - Get medical advice/attention if you feel unwell. P331 - Do NOT induce vomiting. P370+P378 - In case of fire: Use foam/CO2 to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.
Precautionary Statement: Disposal	Dispose of this material and its container to hazardous or special waste collection point.

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Toluene	601-021-00-3	108-88-3	203-625-9		20 - 30%	F; R11 Repr. Cat. 3; R63 Xn; R48/20-65 Xi; R38 R67	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Urea P/W formadehyde, isodutylated		68002-18-6			1 - 10%	Aquatic Chronic 4: H413;	
Toluene	601-021-00-3	108-88-3	203-625-9		20 - 30%	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336;	
n-Butyl acetate (Butyl acetate)	607-025-00-1	123-86-4	204-658-1		10 - 20%	Flam. Liq. 3: H226; STOT SE 3: H336;	
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
Fiddes Acetone Thinners (Acetone)		67-64-1	200-662-2	01-2119471330-49	1 - 10%	EUH066; Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
Butan-1-ol	603-004-00-6	71-36-3	200-751-6	01-2119484630-38	1 - 10%	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336;	
Butanone (Butan-2-one (methyl ethyl ketone))	606-002-00-3	78-93-3	201-159-0		1 - 10%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove casualty from exposure ensuring one's own safety whilst doing so.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Remove contaminated clothing. Wash off immediately with plenty of soap and water.

Fiddes Precat Coloured Lacquer

Revision 2

Revision date 2015-07-08

4.1. Description of first aid measures

Ingestion	DO NOT INDUCE VOMITING.
-----------	-------------------------

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation.
Eye contact	Harmful.
Skin contact	Harmful in contact with skin.
Ingestion	Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention.
Skin contact	Seek medical attention.
Ingestion	Seek medical attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions. Vapour may travel considerable distance to source of ignition and flash back.
--	---

5.2. Special hazards arising from the substance or mixture

	Flammable liquid. Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Keep public away from danger area. Keep upwind.
--	--

6.2. Environmental precautions

	Avoid release to the environment. Refer to special instructions/Safety data sheets. Do not allow product to enter drains.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal.
--	--

6.4. Reference to other sections

	See section 2, 3, 8, 13 for further information.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed in a cool place. Store at temperatures between 5 °C and 18 °C.
--	--

7.3. Specific end use(s)

	No data is available on this product.
--	---------------------------------------

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

	See section 8.2 for further information.
--	--

8.1.1. Exposure Limit Values

Fiddes Precat Coloured Lacquer


Revision 2

Revision date 2015-07-08

8.1.1. Exposure Limit Values

Toluene	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 191
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 384
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls Eye / face protection Skin protection - Handprotection Skin protection - Other Respiratory protection 8.2.3. Environmental exposure controls	
	Ensure adequate ventilation of the working area.
	Wear eye/face protection.
	Chemical resistant gloves (PVC).
	Wear suitable protective clothing.
	Wear suitable respiratory equipment when necessary.
Avoid release to the environment.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Amber
Odour	Characteristic
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	16
Flammability (solid, gas)	No data available
Relative density	0.935
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Insoluble in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
VOC (Volatile organic compounds)	735

SECTION 10: Stability and reactivity

10.1. Reactivity

	No data available.
--	--------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

Fiddes Precat Coloured Lacquer

Revision 2

Revision date 2015-07-08

10.3. Possibility of hazardous reactions

No data is available on this product.

10.4. Conditions to avoid

Heat, sparks and open flames.

10.5. Incompatible materials

Oxidising agents.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and obnoxious fumes.

SECTION 11: Toxicological information**11.1.4. Toxicological Information**

No data available

SECTION 12: Ecological information**12.1. Toxicity**

No data available

12.2. Persistence and degradability

No data is available on this product.

12.3. Bioaccumulative potential

No data is available on this product.

Partition coefficient

Fiddes Precat Coloured Lacquer No data available

12.4. Mobility in soil

No data is available on this product.

12.5. Results of PBT and vPvB assessment

No data is available on this product.

12.6. Other adverse effects

No data is available on this product.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Dispose of as special waste in compliance with local and national regulations.

SECTION 14: Transport information**Hazard pictograms****14.1. UN number**

UN1263

14.2. UN proper shipping name

PAINT RELATED MATERIAL

14.3. Transport hazard class(es)**ADR/RID**

3

Fiddes Precat Coloured Lacquer

Revision 2

Revision date 2015-07-08

14.3. Transport hazard class(es)	
Subsidiary risk IMDG	- 3
Subsidiary risk IATA	- 3
Subsidiary risk	-
14.4. Packing group	
Packing group	II
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
ADR/RID	
Hazard ID	33
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-E
IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
15.2. Chemical safety assessment	
	No data is available on this product.
SECTION 16: Other information	
Other information	
Revision	This document differs from the previous version in the following areas: 2 - 2.1. Classification of the substance or mixture. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal.
Text of risk phrases in Section 3	R11 - Highly flammable. R38 - Irritating to skin.

Fiddes Precat Coloured Lacquer

Revision 2

Revision date 2015-07-08

Other information	
Text of Hazard Statements in Section 3	R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation. R63 - Possible risk of harm to the unborn child. R65 - Harmful: may cause lung damage if swallowed. R67 - Vapours may cause drowsiness and dizziness.
	Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life. EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H302 - Harmful if swallowed. Skin Irrit. 2: H315 - Causes skin irritation. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation.
	Maximum content of VOC
735.	
General information	
	This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy.